

No.	品牌 Brand	型號 Model	動力來源 Type	機身尺寸 Body Size	四角尺寸 Size	最大(鎖緊)扭力 Max Tightening Torque (Nm)	最大(鬆開)扭力 *Nut-Busting Torque (Nm)
1	Matco	MCL1214IWK	12V		1/4"	81	136
2	Chicago Pneumatic	CP8818	12V	Compact 輕型	1/4"	115	NA
3	Ingersoll Rand	W1130	12V	Compact 輕型	3/8"	102	136
4	Bosch	PS82BN	12V	Compact 輕型	3/8"	115	NA
5	ACDelco	AR12104	12V	Compact 輕型	3/8"	122	NA
6	Makita	WT02R1	12V		3/8"	140	NA
7	Snap-on	CT761A	14.4V		3/8"	163	190
8	Makita	XWT12RB	18V	Compact 輕型	3/8"	176	NA
9	Chicago Pneumatic	CP7727	AIR	Compact 輕型	3/8"	190	251
10	Mac Tools	MCF891M1D1	20V	Compact 輕型	3/8"	203	373
11	Ingersoll Rand	2115TIMAX	AIR		3/8"	312	407
12	Milwaukee	2554-22	12V	Compact 輕型	3/8"	339	NA
13	Matco	MT2138	AIR		3/8"	407	502
14	Mac Tools	MPF990381	AIR		3/8"	420	949
15	Snap-on	24411	AIR	Compact 輕型	3/8"	434	NA
16	Hazet	9011M	AIR	Compact 輕型	3/8"	461	461
17	Cornwell	CAT2138	AIR	Compact 輕型	3/8"	475	746
18	Bosch	IDH182	18V	Compact 輕型	1/2"	186	186
19	Hazet	9212M-1	18V	Compact 輕型	1/2"	220	271
20	Chicago Pneumatic	CP7732C	AIR	Compact 輕型	1/2"	386	630
21	Cornwell	CAT4112	AIR	Compact 輕型	1/2"	610	813
22	Hazet	9012M	AIR	Compact 輕型	1/2"	678	1100
23	Mac Tools	MPF990501	AIR		1/2"	786	1898
24	ACDelco	AR12002	20V		1/2"	1001	1491
25	Snap-on	PT850	AIR		1/2"	1098	1613
26	Chicago Pneumatic	CP8849	20V		1/2"	1152	1898
27	Matco	MT2769	AIR		1/2"	1152	1763
28	Ingersoll Rand	2235TIMAX	AIR		1/2"	1220	1830
29	Ingersoll Rand	W7152	20V		1/2"	1356	2034
30	Matco	MCL2012HPIWK	20V		1/2"	1763	1763
31	Chicago Pneumatic	CP7762	AIR	Compact 輕型	3/4"	908	1424
32	Hazet	9013M	AIR	Compact 輕型	3/4"	1085	1890
33	Ingersoll Rand	2145QiMAX	AIR		3/4"	1491	2305
34	Cornwell	CAT3125	AIR		3/4"	1627	2440
35	Matco	MT2234	AIR		3/4"	1627	2440
36	Snap-on	MG1250	AIR		3/4"	1695	2373
37	Matco	SE116	AIR		1"	2169	1627
38	Snap-on	PT1900A	AIR		1"	2440	NA
39	Chicago Pneumatic	CP7782TL-6	AIR		1"	2603	2603
40	Cornwell	CAT6156BP	AIR		1"	2712	NA
41	Hazet	9014P-1	AIR		1"	2712	3399
42	Ingersoll Rand	2850MAX	AIR		1"	2712	2847

*All data collected from Amazon.com, Amazon.de, and/or each brand's official website in April 2019. If you wish to make any corrections or clarifications, kindly e-mail us at: service@tien-i.com

*Nut-Busting Torque refers to the tool's ability to remove a bolt tightened down using methods other than the tool itself. For Nut-Busting Torque, a bolt is tightened with a torque wrench calibrated to 1100 ft-lbs, then removed with the tool being tested.

www.tien-i.com